

Manufactured by:
TENNANT
701 North Lilac Drive
P.O. Box 1452
Minneapolis, MN 55440-1452

MATERIAL SAFETY DATA SHEET

Eco-HPS® 100 / Eco-HTS™ 100 - Part A

100 grams per Liter VOC Compliant Coating



EMERGENCY PHONE NUMBERS:

CHEMTREC: (800) 424-9300 (24 hrs)
CANADA: CANUTEC (613) 996-6666 (24 hrs)

District of Columbia: (202) 483-7616 (24 hrs)
MSDS Requests: (800) 553-8033

PREPARATION INFO:

By: Kevin Hobbie (763) 540-1471 (days)
(612) 834-0118 (mobile)

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.

Issue Date:	June 4, 2009	HAZARD RATING	NFPA	HMS	NFPA	HMS	4 = Extreme	3 = High	0 = Insignificant
Supersedes:	April 22, 2009	Health	2	2	Reactivity	1	2 = Moderate	1 = Slight	COR = Corrosive
Printed:	6/4/2009	Fire	1	1	Special	0			X = Ask supervisor for guidance.

***** I. IDENTIFICATION *****

PRODUCT NAME: Eco-HPS® 100 / Eco-HTS™ 100 - Part A

US DEPT OF TRANSPORTATION (GROUND):

100 grams per Liter VOC Compliant Coating

UN#: None Allocated **PACKAGING GROUP:** Not Applicable

PART NUMBER: 9002618, 9002622

HAZARD CLASSIFICATION: Non Regulated

CHEMICAL FAMILY: Urethane Polymer

SHIPPING NAME: Not Applicable

MATERIAL USE: Urethane Component

***** II. PHYSICAL DATA *****

BOILING POINT:	Not Available	/	Not Available	FREEZE POINT:	Not Available	/	Not Available
DENSITY:	1.2 kg/L			% VOLATILE:	0.7 by wt		
SOLUBILITY IN WATER:	Not Soluble			VAPOR PRESSURE:	Not Available		mm Hg at 20 °C.
ODOR THRESHOLD:	Not Available			pH:	Not Applicable		
PHYSICAL FORM:	Liquid			VAPOR DENSITY:	Heavier		THAN AIR
APPEARANCE AND ODOR:	Neutral/Slight			COEFFICIENT WATER/OIL DISTRIBUTION:	Not Available		
EVAPORATION RATE:	Slower		THAN N-BUTYL ACETATE	VOC g/L (lb/gal):	7 (0.06)		
MECHANICAL IMPACT:	Not Available			STATIC DISCHARGE:	Not Available		

***** III. INGREDIENTS *****

All components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory. Hazardous ingredients, defined as Controlled Products by Canadian WHMIS, are identified by (HZD) after the chemical ingredient. This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and the MSDS contains all of the information required by the CPR.

<u>CHEMICAL</u>	<u>CAS #</u>	<u>% W</u>	<u>OSHA PEL</u> <u>ppm</u>	<u>ACGIH TLV</u> <u>TWA ppm</u>	<u>ACGIH TLV</u> <u>STEL ppm</u>	<u>LD50</u>	<u>LC50</u> <u>INHALATION</u>
Hexamethylene 1,6-diisocyanate, Homopolymer (HDI) (HZD)	28182-81-2	90-100	Not Available	1 mg/m ³	Not Available	350 mg/kg (oral mouse) 593 mg/kg (skin rabbit)	Not Available
Hexamethylene Diisocyanate (HDI) (HZD)	822-06-0	<1	Not Available	0.005	1.00 mg/m ³ (15 min)	>5000 mg/kg (oral rat) >5000 mg/kg (skin rabbit)	390-453 mg/m ³ (4 hr) (rat,male/female)

SARA Title III Section 313 Information: Components present in this product at a level which could require reporting under this statute are:

Hexamethylene-1,6-diisocyanate (HDI) (HZD) - CAS #822-06-0 <0.2% by wt.

California Proposition 65 Information: This product contains the following chemicals designated as cancer and/or reproductive hazards under California Proposition 65.

None

MATERIAL SAFETY DATA SHEET
Eco-HPS 100® / Eco-HTS™ 100 - Part B
100 grams per Liter VOC Compliant Coating



EMERGENCY PHONE NUMBERS:

CHEMTREC: (800) 424-9300 (24 hrs)
CANADA: CANUTEC (613) 996-6666 (24 hrs)

District of Columbia: (202) 483-7616 (24 hrs)
MSDS Requests: (800) 553-8033

PREPARATION INFO:

By: Kevin Hobbie (763) 540-1471 (days)
(612) 834-0118 (mobile)

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.

Issue Date: May 27, 2008	HAZARD RATING	NFPA	HMS	NFPA	HMS	4 = Extreme	3 = High	0 = Insignificant
Supersedes: April 3, 2006	Health	1	1	Reactivity	0	2 = Moderate	1 = Slight	COR = Corrosive
Printed: 6/6/2008	Fire	2	2	Special	0			X = Ask supervisor for guidance.

******* I. IDENTIFICATION *******

PRODUCT NAME: Eco-HPS 100® / Eco-HTS™ 100 - Part B
100 grams per Liter VOC Compliant Coating

US DEPT OF TRANSPORTATION (GROUND):

UN#: None Allocated **PACKAGING GROUP:** Not Applicable

PART NUMBER: 9002619, 9002623

HAZARD CLASSIFICATION: Non Regulated

CHEMICAL FAMILY: Polyol

SHIPPING NAME: Not Applicable

MATERIAL USE: Urethane Component

******* II. PHYSICAL DATA *******

BOILING POINT:	Not Available / Not Available	FREEZE POINT:	Not Available / Not Available
DENSITY:	1.2 kg/L	% VOLATILE:	41 by wt
SOLUBILITY IN WATER:	Not Soluble	VAPOR PRESSURE:	Not Available mm Hg at 20 °C.
ODOR THRESHOLD:	Not Available	pH:	Not Applicable
PHYSICAL FORM:	Liquid	VAPOR DENSITY:	Heavier THAN AIR
APPEARANCE AND ODOR:	Clear/Sweet, Ether-like	COEFFICIENT WATER/OIL DISTRIBUTION:	Not Available
EVAPORATION RATE:	Not applicable THAN N-BUTYL ACETATE	VOC g/L (lb/gal):	467 (3.89)
MECHANICAL IMPACT:	Not Available	STATIC DISCHARGE:	Not Available

******* III. INGREDIENTS *******

All components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory. Hazardous ingredients, defined as Controlled Products by Canadian WHMIS, are identified by (HZD) after the chemical ingredient. This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and the MSDS contains all of the information required by the CPR.

<u>CHEMICAL</u>	<u>CAS #</u>	<u>% W</u>	<u>OSHA PEL ppm</u>	<u>ACGIH TLV TWA ppm</u>	<u>ACGIH TLV STEL ppm</u>	<u>LD50</u>	<u>LC50 INHALATION</u>
Modified Oxazolidine	145899-78-1	5-10	Not Available	Not Available	Not Available	>2000 mg/kg (oral rat) >2000 mg/kg (skin rat)	Not Available
Butyl benzyl phthalate (HZD)	85-68-7	50-60	5 mg/m ³	5mg/m ³	Not Available	20,400 mg/kg (oral rat) >10,000 mg/kg (skin rabbit)	>6.7 mg/L/4hr (rat)
Propylene Carbonate (HZD)	108-32-7	40-50	Not Available	Not Available	Not Available	>5 g/kg (oral rat) >2 g/kg (skin rabbit)	Not Available

SARA Title III Section 313 Information: Components present in this product at a level which could require reporting under this statute are:

Butyl benzyl phthalate (HZD) - CAS #85-68-7 50.10% by wt.

California Proposition 65 Information: This product contains the following chemicals designated as cancer and/or reproductive hazards under California Proposition 65.

Butyl benzyl phthalate (HZD) - CAS #85-68-7 50.10% by wt.

***** IV. FIRE AND EXPLOSIVE HAZARD DATA *****

FLAMMABLE: No (Combustible, WHMIS Class B, Division 3) **FLASH POINT:** 186°F / 85°C Setofflash
FLAMMABLE LIMITS: % LEL: Not Available % UEL: Not Available **AUTOIGNITION TEMPERATURE** Not Available / Not Available
EXTINGUISHING MEDIA: Use National Fire Protection Association (N.F.P.A.) Class B extinguishers (carbon dioxide, dry chemical or foam).

SPECIAL FIRE FIGHTING PROCEDURES:

Water may be ineffective, but may be used to cool closed containers to prevent pressure buildup or possible auto ignition when exposed to extreme heat (fog nozzles preferred). Wear self-contained breathing apparatus.

UNUSUAL FIRE EXPLOSION HAZARD:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces.

***** V. REACTIVITY DATA *****

STABILITY: Stable **HAZARDOUS POLYMERIZATION (May Occur/Will Not Occur):** Will Not

CONDITIONS TO AVOID: Excessive heat and moisture.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents. In the presence of moisture/water, isobutyraldehyde may be produced. Isobutyraldehyde vapors are heavier than air and forms an explosive mixture with it.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide and nitrogen oxides in varying quantities.

***** VI. HEALTH HAZARD DATA *****

EFFECTS OF OVEREXPOSURE: **THRESHOLD LIMIT VALUE - See Section III for individual ingredients.**

PRIMARY ROUTES OF ENTRY: Inhalation & Skin Contact

SKIN CONTACT/ABSORPTION: Contains materials which may cause skin irritation.

EYE CONTACT: Contains materials which may cause eye irritation. During application of this product, contact lenses should NOT be worn.

INGESTION (Swallowing):

Contains materials which can cause a burning sensation, vomiting, diarrhea, drowsiness and tissue damage. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.

INHALATION (Breathing):

Under normal product use, inhalation exposure should be minimal. Contains materials which have the potential to cause headaches, nausea, dizziness and respiratory tract irritation upon inhalation of vapors heated to high temperatures.

SUPPLEMENTAL HEALTH INFORMATION:

Ingredients are NOT carcinogenic, based on the International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) lists. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

***** VII. EMERGENCY AND FIRST AID PROCEDURES *****

SKIN CONTACT: IMMEDIATELY wash exposed areas with soap and water for 15 minutes. Seek medical attention if irritation develops and persists. Wash clothing before reuse.

EYE CONTACT: Flush immediately with water for 15 minutes; CALL A PHYSICIAN.

INGESTION (Swallowing): CALL A PHYSICIAN OR POISON CONTROL CENTER. DO NOT attempt to induce vomiting.

INHALATION (Breathing): Remove to fresh air. If breathing difficulty persists or occurs later, consult a physician.

***** VIII. PREVENTIVE MEASURES *****

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep spectators away. Floor may be slippery; use care to avoid falling. Dike and contain the spill with inert material (sand, earth, fuller's earth, etc.) and if appropriate, transfer the liquid and solid diking material to separate containers for recovery or disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Wash clothing before reuse. Keep spill out of all sewers and open bodies of water.

WASTE DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION and VENTILATION:

Use with adequate ventilation. Where ventilation is inadequate, wear a chemical respirator approved for organic vapors. Use NIOSH 42 CFR 84 approved respirator.

Provide local exhaust ventilation when appropriate to control employee exposure and to keep vapor concentrations below TLV (see Section III).

PROTECTIVE GLOVES (specify type):

Impervious gloves; i.e., rubber

EYE PROTECTION (specify type)

Chemical splash goggles

SKIN PROTECTION:

Protective clothing, such as uniforms or coveralls and protective gloves. Launder clothing when soiled.

SPECIAL PRECAUTIONS:

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORAGE:

Store inside in a cool (below 100°F or 37.5°C), dry place. Store large quantities in buildings designed and protected for storage of NFPA Class II liquids.

OTHER PRECAUTIONS:

Do not take internally. Avoid prolonged contact with skin; contaminated clothing should be removed immediately. Avoid free fall of liquid in excess of a few inches.

MATERIAL SAFETY DATA SHEET

Eco-HTS™ 100 / Eco-UVC™ Part C

100 grams per Liter VOC Compliant Coating / InstaCure™ Solution - Commercial & Industrial



EMERGENCY PHONE NUMBERS:

CHEMTREC: (800) 424-9300 (24 hrs)
CANADA: CANUTEC (613) 996-6666 (24 hrs)

District of Columbia: (202) 483-7616 (24 hrs)
MSDS Requests: (800) 553-8033

PREPARATION INFO:

By: Kevin Hobbie (763) 540-1471 (days)
(612) 834-0118 (mobile)

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.

Issue Date: October 7, 2008	HAZARD RATING	NFPA	HMS	NFPA	HMS	4 = Extreme	3 = High	0 = Insignificant
Supersedes: June 6, 2008	Health	0	0	Reactivity	0	2 = Moderate	1 = Slight	COR = Corrosive
Printed: 1/13/2009	Fire	0	0	Special	0			X = Ask supervisor for guidance.

******* I. IDENTIFICATION *******

PRODUCT NAME: Eco-HTS™ 100 / Eco-UVC™ Part C
100 grams per Liter VOC Compliant Coating / InstaCure™ Solution - Commercial & Industrial

US DEPT OF TRANSPORTATION (GROUND):
UN#: None Allocated **PACKAGING GROUP:** Not Applicable

PART NUMBER: 9002620, 9002624, Special

HAZARD CLASSIFICATION: Non Regulated

CHEMICAL FAMILY: Aluminum Oxide

SHIPPING NAME: Not Applicable

MATERIAL USE: Component in Floor Coating for Concrete

******* II. PHYSICAL DATA *******

BOILING POINT:	Not Available	/	Not Available	FREEZE POINT:	Not Available	/	Not Available
DENSITY:	4.0 kg/L			% VOLATILE:	0 by wt		
SOLUBILITY IN WATER:	Not Soluble			VAPOR PRESSURE:	Not Available		mm Hg at 20 °C.
ODOR THRESHOLD:	Not Available			pH:	Not Available		
PHYSICAL FORM:	Solid			VAPOR DENSITY:	Not Available		THAN AIR
APPEARANCE AND ODOR:	Granular - White/None			COEFFICIENT WATER/OIL DISTRIBUTION:	Not Available		
EVAPORATION RATE:	Not Available		THAN N-BUTYL ACETATE	VOC g/L (lb/gal):	0 (0.00)		
MECHANICAL IMPACT:	Not Available			STATIC DISCHARGE:	Not Available		

******* III. INGREDIENTS *******

All components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory. Hazardous ingredients, defined as Controlled Products by Canadian WHMIS, are identified by (HZD) after the chemical ingredient. This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and the MSDS contains all of the information required by the CPR.

<u>CHEMICAL</u>	<u>CAS #</u>	<u>% W</u>	<u>OSHA PEL</u> <u>ppm</u>	<u>ACGIH TLV</u> <u>TWA ppm</u>	<u>ACGIH TLV</u> <u>STEL ppm</u>	<u>LD50</u>	<u>LC50</u> <u>INHALATION</u>
Nonfibrous Aluminum Oxide (HZD)	1344-28-1	60-70	10 mg/m ³ , 5 mg/m ³ (respirable dust)	10 mg/m ³	Not Available	Not Available	Not Available
Glass Oxide	65997-17-3	30-40	Nuisance Dust: 15 mg/m ³ ; Resp. Fraction: 5 mg/m ³	10 mg/m ³	Not Available	Not Available	Not Available

SARA Title III Section 313 Information: Components present in this product at a level which could require reporting under this statute are:
None

California Proposition 65 Information: This product contains the following chemicals designated as cancer and/or reproductive hazards under California Proposition 65.
None

***** IV. FIRE AND EXPLOSIVE HAZARD DATA *****

FLAMMABLE: No **FLASH POINT:** Not Available / Not Available Setofflash
FLAMMABLE LIMITS: % LEL: Not Available % UEL: Not Available **AUTOIGNITION TEMPERATURE** Not Available / Not Available
EXTINGUISHING MEDIA: Will not burn. May be used to extinguish fires.
SPECIAL FIRE FIGHTING PROCEDURES:
None. Will not burn.
UNUSUAL FIRE EXPLOSION HAZARD:
None known.

***** V. REACTIVITY DATA *****

STABILITY: Stable **HAZARDOUS POLYMERIZATION (May Occur/Will Not Occur):** Will Not
CONDITIONS TO AVOID: None.
INCOMPATIBILITY (materials to avoid): None known.
HAZARDOUS DECOMPOSITION PRODUCTS: None known.

***** VI. HEALTH HAZARD DATA *****

EFFECTS OF OVEREXPOSURE: **THRESHOLD LIMIT VALUE - See Section III for individual ingredients.**
PRIMARY ROUTES OF ENTRY: Inhalation & Skin Contact
SKIN CONTACT/ABSORPTION: Not absorbed through skin. May cause abrasions.
EYE CONTACT: Contains materials which may cause eye irritation and abrasion. During application of this product, contact lenses should NOT be worn.
INGESTION (Swallowing):
No known effects for normal, incidental ingestion.
INHALATION (Breathing):
May cause coughing or shortness of breath. Chronically may affect breathing capacity.
SUPPLEMENTAL HEALTH INFORMATION:
All ingredients are NOT carcinogenic, based on the International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP).

***** VII. EMERGENCY AND FIRST AID PROCEDURES *****

SKIN CONTACT: Wash thoroughly with soap and water. Seek medical attention if irritation persists.
EYE CONTACT: Flush immediately with water for 15 minutes. Obtain medical attention if discomfort persists.
INGESTION (Swallowing): Dilute with two glasses of water. CALL A PHYSICIAN OR POISON CONTROL CENTER.
INHALATION (Breathing): Remove to fresh air. If breathing difficulty persists or occurs later, consult a physician.

***** VIII. PREVENTIVE MEASURES *****

SPILL OR LEAK PROCEDURES **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**
Sweep or scoop up and put in disposal container. Collect using dustless methods (HEPA vacuum or flush with water) to minimize generation of airborne respirable dust.
WASTE DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.
SPECIAL PROTECTION INFORMATION
RESPIRATORY PROTECTION and VENTILATION:
Avoid inhalation of dust by wearing a single use dust mask or respirator with cartridge (NIOSH TC 21C-132).
Local exhaust, vented hoods with dust collection.
PROTECTIVE GLOVES (specify type): **EYE PROTECTION (specify type)**
Impervious gloves; i.e., rubber Chemical splash goggles
SKIN PROTECTION: Impervious gloves; i.e., rubber
SPECIAL PRECAUTIONS: **PRECAUTIONS TO BE TAKEN IN HANDLING OR STORAGE:**
Store inside in a cool (below 100°F or 37.5°C), dry place.
OTHER PRECAUTIONS: Do not take internally.

***** IV. FIRE AND EXPLOSIVE HAZARD DATA *****

FLAMMABLE: No **FLASH POINT:** >200°F / >93°C Setflash
FLAMMABLE LIMITS: % LEL: Not Available % UEL: Not Available **AUTOIGNITION TEMPERATURE** Not Available / Not Available
EXTINGUISHING MEDIA: Use National Fire Protection Association (N.F.P.A.) Class B extinguishers (carbon dioxide, dry chemical or foam).
SPECIAL FIRE FIGHTING PROCEDURES:
Water may be ineffective, but may be used to cool closed containers to prevent pressure buildup or possible auto ignition when exposed to extreme heat (fog nozzles preferred). Wear self-contained breathing apparatus.
UNUSUAL FIRE EXPLOSION HAZARD:
Product will burn under fire conditions. Under fire conditions, toxic, corrosive fumes are emitted.

***** V. REACTIVITY DATA *****

STABILITY: Stable **HAZARDOUS POLYMERIZATION (May Occur/Will Not Occur):** Will Not
CONDITIONS TO AVOID: Excessive heat.
INCOMPATIBILITY (materials to avoid): Water, strong acids, bases and oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide and nitrogen oxides in varying quantities.

***** VI. HEALTH HAZARD DATA *****

EFFECTS OF OVEREXPOSURE: **THRESHOLD LIMIT VALUE - See Section III for individual ingredients.**
PRIMARY ROUTES OF ENTRY: Inhalation & Skin Contact
SKIN CONTACT/ABSORPTION: Irritant. May be harmful if absorbed through the skin. May cause allergic reaction.
EYE CONTACT: Contains materials which may cause eye irritation. During application/use of this product, contact lenses should NOT be worn.
INGESTION (Swallowing):
May be harmful if swallowed.
INHALATION (Breathing):
May be harmful if inhaled. May cause shortness of breath, headache, nausea, vomiting, respiratory tract irritation.
SUPPLEMENTAL HEALTH INFORMATION:
Ingredients are NOT carcinogenic, based on the International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) lists.
Sensitization: HDI is a pulmonary and dermal sensitizer in animals and humans.
The HDI polymer has an extremely low vapor pressure, and in cases where HDI based products are roller (not spray) applied, the amount of free HDI should not exceed known TLV of 0.005 ppm. This statement relies on the fact that the product is applied at the recommended application temperature (65-90 deg. F.), and air movement across the floor surface (less than 25 linear feet per minute). Urethanes containing free diisocyanate monomer should always be roller applied and never sprayed.

***** VII. EMERGENCY AND FIRST AID PROCEDURES *****

SKIN CONTACT: IMMEDIATELY wash exposed areas with soap and water for 15 minutes. Seek medical attention if irritation develops and persists. Wash clothing before reuse.
EYE CONTACT: Flush immediately with water for 15 minutes; CALL A PHYSICIAN.
INGESTION (Swallowing): If victim is conscious and alert, give 2-3 glasses of water to drink and induce vomiting by touching back of throat with a finger. Do not induce vomiting or give anything by mouth to an unconscious person. Seek immediate medical attention. Do not leave victim unattended. Vomiting may occur spontaneously. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. If vomiting occurs and the victim is conscious, give water to further dilute the chemical.
INHALATION (Breathing): Remove to fresh air. Restore breathing if required. If breathing difficulty persists or occurs later, consult a physician.

***** VIII. PREVENTIVE MEASURES *****

SPILL OR LEAK PROCEDURES **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**
Keep spectators away. Floor may be slippery; use care to avoid falling. Dike and contain the spill with inert material (sand, earth, fuller's earth, etc.) and if appropriate, transfer the liquid and solid diking material to separate containers for recovery or disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Wash clothing before reuse. Keep spill out of all sewers and open bodies of water.
WASTE DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.
SPECIAL PROTECTION INFORMATION
RESPIRATORY PROTECTION and VENTILATION:
Use with adequate ventilation. Where ventilation is inadequate, wear a chemical respirator approved for organic vapors. Use NIOSH 42 CFR 84 approved respirator.
Provide local exhaust ventilation when appropriate to control employee exposure and to keep vapor concentrations below TLV (see Section III).
PROTECTIVE GLOVES (specify type): Impervious gloves; i.e., rubber
EYE PROTECTION (specify type): Chemical splash goggles
SKIN PROTECTION: Protective clothing, such as uniforms or coveralls and protective gloves. Launder clothing when soiled.
SPECIAL PRECAUTIONS: **PRECAUTIONS TO BE TAKEN IN HANDLING OR STORAGE:**
Store inside in a cool (below 100°F or 37.5°C), dry place.
OTHER PRECAUTIONS: Do not take internally. Avoid prolonged contact with skin; contaminated clothing should be removed immediately. Avoid free fall of liquid in excess of a few inches.